

# GT3260R

## Mobile Radial Conveyor



### Main Conveyor

- 58' 6" (18m) long x 32" (800mm) wide
- Variable angle Troughing Rollers. 3 Roll set x 4" (102mm) dia.
- 4" (102mm) Plain return rollers.
- 13" (300mm) Head pulley
- 11" (280mm) Tail pulley complete with self-cleaning plow scraper
- Secondary spring mounted polyurethane blade scraper
- 20" (500mm) Bolt on Feed boot Extensions

### Frame

- Fully enclosed power unit with hinged access doors
- Hydraulic folding head section as standard
- Manual folding tail section
- Hydraulic raise/ lower head and tail section
- Heavy duty track mounted Chassis for complete mobility

### Plant Capacity

- Up to 330 USTPH (300 MTPH). (Capacity will vary with conditions)

### Power and Hydraulics

- Standard/EU Stage V /USA Tier 4
- Deutz TD2.2 L3 Electronic 3 Cylinder, 50HP (36.9KW) @ 2200 RPM
- 53 gallon (200 liters) fuel tank. Lockable with side mounted level gauge.
- 50 gallon (185 liters) hydraulic reservoir with in line return filter. Lockable with side mounted level gauge

- Engine mounted hydraulic pump to operate all machine functions.
- Hydraulic operated crawler tracks with pendant control for Machine relocation.
- NEMA-4 Rated instrument panel: Hour meter, emergency stops, cold start
- Single Orbital drive motor on main conveyor
- 1 x Internal hydraulic wheel drive for powered radial travel
- Wireless Radio remote control for radial left / right, raise lower head and tail

### Options

- Full length side skirting
- 1/4" (6mm) Hardened steel liners
- Upgraded belts
- Radio Remote
- Oil Cooler
- Impact center rollers in feed boot

### Engine Options

- EU STAGE IIIA/ Tier 3 – CAT C 2.2, 50Hp (37kW) Suitable for Lesser Regulated Countries
- EU STAGE IIIB/ Tier 4 - Deutz D2.9 L4 Electronic 4 Cylinder, 50Hp (36.4 kW) (USA ONLY)